



種類	呼び名	寸法 (mm)														参考重量 (kg)	縦鉄筋					
		a	b	c	d	d'	e	f	g	h	t	t'	r	l	横鉄筋							
															外側鉄筋		内側鉄筋					
径 (mm)	数量 (本)	径 (mm)	数量 (本)	径 (mm)	数量 (本)																	
1種	300 A	300	280	300	40	55	60	60	360	20	95	120	50	2000	341	4.0	11	4.0	10	—	—	
	300 B	300	270	400	40	55	65	65	360	20	95	120	50	2000	411	4.0	13	4.0	10	—	—	
	400 A	400	370	400	40	55	65	65	460	20	110	135	50	2000	448	4.0	14	5.0	10	—	—	
3種		250	230	250	45	55	65	65	300	30	90	120	50	2000	326	4.0	11	D6	14	—	—	
		300	280	300	50	55	70	70	360	30	95	140	50	2000	410	4.0	11	D6	16	—	—	
	300 B	300	270	400	50	55	70	70	330	40	95	140	50	2000	462	4.0	15	D6	19	D6	10	
	300 C	300	260	500	50	55	80	80	340	40	95	140	50	2000	573	4.0	17	D6	21	D6	11	
	400 A	400	370	400	55	55	70	70	430	40	110	140	50	2000	506	4.0	17	D6	23	D6	12	
	400 B	400	360	500	55	55	80	80	440	40	110	140	50	2000	622	4.0	19	D6	23	D6	12	
500 A	500	460	500	60	60	80	80	540	40	125	155	50	2000	686	4.0	20	D6	23	D6	12		

名称	道路側溝M (無騒音)	縮尺	1/20	図面	A4	作成日	17/9/27	 和光産業株式会社
規格	—	図番	170927-11-0		区分	製・配筋図		