



呼び	寸法 (mm)															参考重量(kg)		縦鉄筋		横鉄筋		
	a	b	c	d	e	h	r	l	cs	cs	ds	es	hs	l ₁	l=2000	l=1000	径(mm)	数量(本)	径(mm)	数量(本)		
																				l=2000	l=1000	
200	200	170	205	30	35	150	30	2000	1000	276	243	27	30	193	50	96	50	3.2	8	2.6	21	11
250	250	215	250	30	35	175	30	2000	1000	326	288	27	30	218	50	114	59	3.2	9	2.6	23	12
300	300	260	300	30	40	200	40	2000	1000	376	338	27	30	248	50	144	72	3.2	9	3.2	21	11
350	350	300	345	35	45	235	50	2000	1000	436	388	32	35	288	50	191	102	3.2	10	3.2	23	12
400	400	345	395	40	50	260	50	2000	1000	496	438	32	35	318	50	239	120	4.0	10	4.0	21	11
450	450	390	440	40	50	295	50	2000	1000	546	483	32	35	353	50	266	138	4.0	12	4.0	21	11
500	500	435	490	45	55	320	60	2000	1000	606	538	36	40	383	50	319	170	5.0	12	4.0	23	12
550	550	475	535	45	60	355	60	2000	1000	656	588	41	45	423	50	379	200	5.0	12	5.0	21	11
600	600	520	580	45	60	380	60	2000	1000	706	633	41	45	448	50	400	219	5.0	12	5.0	-	11
650	650	565	630	45	65	415	70	-	1000	756	683	41	45	488	50	-	244	5.0	13	5.0	-	12
700	700	610	680	50	70	440	70	-	1000	816	733	41	45	518	50	-	281	5.0	13	5.0	-	12
800	800	695	770	50	75	490	70	-	1000	916	828	45	50	573	50	-	332	5.0	14	6.0	-	11
900	900	785	870	55	85	550	80	-	1000	1026	933	50	55	643	50	-	420	5.0	14	6.0	-	12
1000	1000	875	965	55	90	600	80	-	1000	1126	1033	54	60	693	50	-	483	5.0	15	6.0	-	13

※横鉄筋本数には、ソケット部鉄筋1本を含む。

名称	ベンチフレーム	縮尺		図面	A4	作成日	07/3/1	和光産業株式会社
規格		図番	-			区分	製配筋図	